

NB-1	C-1
15	65
20	75
25	89
40	102
50	114
80	140
100	165
150	203
200	229
250	250
300	250

## DIMENSIONAL STANDARDS:

ALL DIMENSION ARE IN MM OTHERWISE SPECIFIED & AS PER ANSI B16.9

## 2) MATERIAL OF CONSTRUCTION:

- A) TEE ARE SUPPLIED EITHER IN FEP OR PFA LINED DEPENDINIG ON PROCESS LIQUID HANDLED & AS PER STANDARD RESIN SPECIFICATION. ASTM D 2116 TYPE-||| & ASTM D 3307 TYPE || RESPECTIVELY.
- B) DUCTILE CAST IRON CONFIRMS TO ASTM A-395 OR S.G IRON
  CONFIRMS TO ASTM A-536(60-40-18) OR CAST CARBON STEEL
  CONFIRMS TO ASTM A-216 GR.WCB. OR FABRICATED FROM 106 GR. B SCH 40 PIPE
- C) TEE ARE BEING SUPPLIED WITH FIXED FLANGES. HOWEVER IT CAN BE SUPPLIED WITH LOOSE FLANGES AS PER INDIVIDUAL CUSTOMER'S REQUIREMENT & CONFIRMS TO ASTM A-105 OR OR IS-2062.
- D) GTPL OFFERS SS FITTINGS AS PER INDIVIDUAL CUSTOMER'S REQUIREMENT.

