



NB-1	NB-2	TH
20	15	35
25	15	35
25	20	35
40	25	35
50	25	35
50	40	35
80	25	45
80	40	45
80	50	45
100	25	45
100	40	45
100	50	45
100	80	45

NB-1	NB-2	TH
150	25	55
150	40	55
150	50	55
150	80	55
150	100	55
200	25	55
200	40	55
200	50	55
200	80	55
200	100	55
200	150	55
250	25	55
250	40	55
250	50	55
250	80	55
250	100	55
250	150	55
250	200	55
300	25	55
300	40	55
300	50	55
300	80	55
300	100	55
300	150	55
300	200	55
300	250	55
350	25	55
350	40	55
350	50	55

NOTES: -

- 01) DIMENSIONAL STANDARDS:
 A) ALL DIMENSIONS ARE IN MM OTHERWISE SPECIFIED & AS PER ANSI B16.9 'B' FLANGES ARE DRILLED AS PER DIN, ASA, JIS OR BS STANDARDS AS PER INDIVIDUAL CUSTOMER'S REQUIREMENT.
 02) MATERIAL OF CONSTRUCTION:
 A) REDUCING FLANGES ARE FROM PTFE & AS PER STANDARD RESIN SPEC. ASTM D 1457 TYPE II & ASTM D-4894 & 5 TYPE-II OR FEP D-2116 TYPE-III OR PFA D-3307 TYPE-II
 B) FLANGES CONFIRMS TO IS-2062 OR DUCTILE CART IRON CONFIRMS TO ASTM-A-395 OR CI TO GR.20.
 D) GTPL OFFERS SS FITTINGS AS PER INDIVIDUAL CUSTOMER'S REQUIREMENT.

Galaxy Thermoplast Pvt. Ltd.

PTFE, PFA, FEP, ECTFE, PVDF, HDPE, PP lined equipment & other products



CLIENT. :-	DRAWN. KK	24.10.06
REF. :-	CHKD. AK	24.10.06
P.O. NO. :-	APPD. CLIENT.	
EQPT. NO. :-	QTY. :	SCALE : AS NOTED. SHEET: 1 OF 1
TITLE. : FEP/PFA LINED REDUCING FLANGE	DRG. NO. : GTPL-006	
	REV. :	0 1 2 3 4