


NB-1	NB-2	C-1	LINER THICKNESS
15	15	65	3.0
20	20	75	3.0
25	25	89	3.2
40	40	102	3.2
50	50	114	3.5
50	25	114	3.5
50	40	114	3.5
80	25	140	3.5
80	40	140	3.5
80	50	140	3.5
80	80	140	3.5
100	100	165	4.0
100	25	165	4.0
100	40	165	4.0
100	50	165	4.0
100	80	165	4.0
150	50	203	5.0
150	100	203	5.0
150	150	203	5.0
200	200	229	5.0
250	250	279	5.0
300	300	305	5.0

DIMENSIONAL STANDARDS :

ALL DIMENSION ARE IN MM OTHERWISE SPECIFIED & AS PER ANSI B16.9

2) MATERIAL OF CONSTRUCTION:

- A) TEE ARE SUPPLIED EITHER IN FEP OR PFA LINED DEPENDING ON PROCESS LIQUID HANDLED & AS PER STANDARD RESIN SPECIFICATION. ASTM D 2116 TYPE-III & ASTM D 3307 TYPE II RESPECTIVELY.
- B) DUCTILE CAST IRON CONFIRMS TO ASTM A-395 OR S.G IRON CONFIRMS TO ASTM A-536(60-40-18) OR CAST CARBON STEEL CONFIRMS TO ASTM A-216 GR.WCB. OR FABRICATED FROM 106 GR. B SCH 40 PIPE
- C) TEE ARE BEING SUPPLIED WITH FIXED FLANGES. HOWEVER IT CAN BE SUPPLIED WITH LOOSE FLANGES AS PER INDIVIDUAL CUSTOMER'S REQUIREMENT & CONFIRMS TO ASTM A-105 OR OR IS-2062.
- D) GTPL OFFERS SS FITTINGS AS PER INDIVIDUAL CUSTOMER'S REQUIREMENT.

Galaxy Thermoplast Pvt. Ltd.			
PTFE, PFA, FEP, ECTFE, PVDF, HDPE, PP lined equipment & other products			
CLIENT. : ---	DRAWN. KK	24.10.06	
REF. : -	CHKD. AK	24.10.06	
P.O. NO. :-	QTY. :	SCALE : AS NOTED. SHEET: 1 OF 1	
EQPT. NO. :-	DRG. NO. : GTPL-005		
TITLE. : FEP/PFA LINED UNEQUAL TEE	REV. :	0	1 2 3 4